

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**



(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
21 June 2001 (21.06.2001)

PCT

(10) International Publication Number  
**WO 01/45061 A2**

(51) International Patent Classification<sup>7</sup>: **G07G**

(21) International Application Number: **PCT/IB00/01872**

(22) International Filing Date:  
14 December 2000 (14.12.2000)

(25) Filing Language: **English**

(26) Publication Language: **English**

(30) Priority Data:  
09/461.353 15 December 1999 (15.12.1999) **US**

(71) Applicant: **NOKIA CORPORATION** [FI/FI]; Keilalahdentie 4, FIN-02150 Espoo (FI).

(71) Applicant (for LC only): **NOKIA INC.** [US/US]; 6000 Connection Drive, Irving, TX 75039 (US).

(72) Inventor: **RISSANEN, Jussi**; Pajalahdentie 6 A 18, FIN-00200 Helsinki (FI).

(74) Agents: **BRUNDIDGE, Carl, I. et al.**; Antonelli, Terry, Stout & Kraus, LLP, Suite 1800, 1300 N. Seventeenth Street, Arlington, VA 22209 (US).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

**Published:**

— Without international search report and to be republished upon receipt of that report.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **WIRELESS ELECTRONIC COUPONING TECHNIQUE**

(57) Abstract: An electronic couponing technique includes transferring coupon information, which may include a coupon ID (identification) to a first portable terminal and storing same therein. The portable terminal displays a representation of the transferred coupon information on a display thereof. The stored coupon information may be transferred from the portable terminal to another terminal for redemption. The stored coupon information may also be transferred from the portable terminal to another portable terminal. Various schemes may be used to transfer the coupon information including a Bluetooth low-range radio link or an optical bar code scanner scanning an optical bar code or an infrared link or a wireless link from the portable terminal. The Internet or wireless LAN (Local Area Network) may also be used in transferring the coupon information to and from the various terminals.

WO 01/45061 A2

## WIRELESS ELECTRONIC COUPONING TECHNIQUE

TECHNICAL FIELD

The present invention relates to the field of telecommunications/mobile terminals. More particularly, the present invention relates to a mobile terminal capable of downloading, or scanning, or collecting, and viewing, or transmitting, and using coupons.

5           There has been a problem of how to handle transactions including coupons in retail stores. Coupons in a paper format require manual operation by the cashier at the retail store, taking up valuable customer service time, thus increasing the length of checkout lines, resulting in need of more personnel and thus expenses. Also the logistics involved in further mailing the paper coupons to respective manufacturers for validation and related cash  
10       reimbursements to retail stores tie up significant amounts of effort and workload.

Also, at the customer end, there is the problem of how to keep track of, store, find and use the right coupons when visiting retail stores when buying the goods in question. Usually the coupon usage operation by the consumer has been as follows (an example):

15           A consumer reads a newspaper and finds a coupon insert. The consumer enters a retail store and collects the goods to be purchased. At the checkout counter, the goods are read by a bar code scanner. The consumer gives the cashier the coupons that are valid and the cashier enters the discount, either by bar code scanner or manually. The consumer thus receives a discount on the specific products mentioned in the coupons.

20           After that, the retail store gathers all the coupons, sorts them out and send them to their respective manufacturers who then credit the retail store's account on respective sums of the discount (in the case of manufacturer reimbursed coupons).

On the larger view there is a rising problem and challenge of how to bring meaningful and acceptable marketing communication, direct marketing, direct response

marketing and advertising messages to new wireless mobile terminals that are emerging. These wireless terminals include mobile phones, personal digital assistants (PDAs) with network connectivity, smart phones and other wireless internet appliances. The wireless couponing system, methodology and apparatus is a new method of providing advertisers and  
5 marketers access to their target audiences using wireless terminals.

Presently, there are two types of Internet coupons in use in retail sales.

In one type of Internet coupon arrangement, Internet coupons are downloaded from the Internet by a user and printed on the user's printer. This eliminates the coupon distribution problem from the manufacturer or retail store to the user but does not eliminate  
10 the use of paper coupons from the user to the retail store and optionally to the manufacturer.

Another type of Internet coupon arrangement allows the downloading of coupons from the Internet to a smart card of the user. The use of smart cards having coupons stored therein requires special hardware and the coupons stored in the smart card are not easily viewed by the user while in a retail store.

## 15 DISCLOSURE OF THE INVENTION

In carrying out one technique of the present invention, there is a system of infrastructure comprising and supporting wireless coupons that may be downloaded, viewed, credited (used) in electronic format throughout their distribution life cycle. The coupons are stored, carried and used in a wireless mobile terminal such as a mobile phone. The electronic  
20 coupons may be delivered to the terminal by methods including: they may be downloaded to the terminal from the Internet; they may be pushed to the terminal by e-mail-type messages; they may be downloaded to the terminal by a short-range radio link such as Bluetooth or they may be scanned from a printed paper by using a (built in or external) scanner in a mobile terminal, or via an infrared link or by other methods. They may also be downloaded from a  
25 wireless LAN connection.

An important distinction from previous Internet coupons and print coupons is the fact that the coupon files are stored in the memory of the mobile terminal, or a coupon ID number string is stored in the mobile terminal and the visual representation may be downloaded separately from a network server as needed or when excess bandwidth capacity exists. Thus, the coupon files are easily carried by the consumer at all times, and are readily available as the need rises (like when visiting a retail store, a restaurant, gas station, etc.). During a visit to a retail outlet, the consumer takes out his/her mobile terminal, initiates a coupon match sequence that compares the coupon files stored in the terminal with the promotions effective at the retail outlet. If a match is found, i.e., the consumer carries an electronic coupon that justifies a discount, the point of sale (POS) terminal calculates a discount to the prices of the goods to be purchased, or grants other specified benefits to the coupon bearer. The mobile terminal and the POS terminal may exchange the electronic coupon information in the following ways: a wireless digital short-range radio link such as Bluetooth, via an infrared data link, or via bar code scanning by the POS terminal from the mobile terminal display.

### **BRIEF DESCRIPTION OF THE DRAWINGS**

The foregoing and a better understanding of the present invention will become apparent from the following detailed description of example embodiments and the claims when read in connection with the accompanying drawings, all forming a part of the disclosure of this invention. While the foregoing and following written and illustrated disclosure focuses on disclosing example embodiments of the invention, it should be clearly understood that the same is by way of illustration in example only and the invention is not limited thereto. The spirit and scope of the present invention are limited only by the terms of the appended claims.

Fig. 1 is a flowchart of a couponing system in accordance with the present invention.

Fig. 2 illustrates one possible implementation of coupon browsing on a wireless terminal.

Fig. 3 illustrates the general architecture of the wireless couponing technique of the present invention.

5 Fig. 4 illustrates the data flow from a wireless terminal to a point of sale terminal via Bluetooth.

Fig. 5 illustrates the data flow from a wireless terminal to a point of sale terminal via optical bar code scanning.

10 Fig. 6 illustrates the data flow from a wireless terminal to a point of sale terminal via an infrared link.

Fig. 7 illustrates the flow from a wireless terminal to a point of sale terminal via GPRS (general packet radio service).

Fig. 8 illustrates the data flow from a wireless terminal to a wireless terminal via GPRS.

15 Fig. 9 illustrates the data flow from a wireless terminal to a wireless terminal via an infrared link.

Fig. 10 illustrates the data flow from a wireless terminal to a wireless terminal via Bluetooth.

20 Fig. 11 illustrates the data flow from a wireless terminal to a wireless terminal utilizing optical bar code scanning.

Fig. 12 illustrates optically scanning a coupon ID from a print media source.

Fig. 13 illustrates a Bluetooth radio link transmitted coupon.

Fig. 14 illustrates a GPRS network transmitted coupon.

#### **BEST MODE FOR CARRYING OUT THE INVENTION**

25 Fig. 1 is a flowchart of a couponing system in accordance with the present invention.

In Step 100, a coupon is created and delivered to a network server. The various attributes of the coupon are inputted to the server by either a manufacturer of the product or products mentioned in the coupon or are inputted to the server from the offices of a retailer store. In both cases, the purpose of providing discount coupons is to increase sales by providing the user with an additional incentive to purchase the product or products mentioned in the coupon. In the case of coupons being offered by a retailer, the incentive offered by the coupon increases the volume of traffic of potential buyers which usually results in increased sales.

In Step 110, the coupon is electronically delivered to the wireless terminal using one of several optional methods which will be discussed later.

In Step 120, the terminal processes the electronically transmitted coupon by handling, categorizing, storing, and enabling browsing by the user.

Fig. 2 illustrates one possible implementation of coupon browsing on a display of a wireless terminal. This is but one possible example of the wireless terminal display during coupon browsing. It is, of course, understood that other possibilities exist depending on the capability of the wireless terminal.

Returning to Fig. 1, in Step 130, the wireless terminal contains an additional feature not available with paper coupons, namely, the ability to forward the electronically transmitted coupon to another wireless terminal or to in effect multiply the electronically transmitted coupon by forwarding it to several other wireless terminals. This allows for the wider distribution of the electronically transmitted coupon at no additional cost to the manufacturer or retailer issuing the coupon and is analogous to word-of-mouth advertising. Word-of-mouth advertising is a very powerful advertising tool in that a satisfied customer disseminates information about a product to other potential customers who value the opinion of the satisfied customer.



In Step 140, the user of the billable terminal can transfer the electronically transmitted coupon to the point-of-sale terminal of the retailer via one of several different methods which will be discussed in detail later.

5 In Step 150, the point-of-sale terminal validates the electronically transmitted coupon and electronically redeems it by providing an immediate discount to the customer in accordance with the requirements of the coupon.

In Step 160, the point-of-sale terminal reports the redemption of the coupon to the issuer of the coupon such as the manufacturer in the case of manufacturer coupons and to the retailer's office in the case of retailer coupons.

10 Fig. 3 illustrates the general architecture of the wireless couponing technique of the present invention.

The coupon service server 200 receives and stores the attributes of the various coupons to be disseminated to the wireless terminals.

15 A coupon would include the discount/benefit information (e.g. which specific product, and which product family and in what combination, etc.), the forwardability and multiplyability information (that is, whether the electronic coupon could be forwarded to one or more other wireless terminals), the validity time period, the usage time period (e.g., during office hours, etc.). The textual and visual/audio representation of the coupon may be forwarded together or separately from the coupon service server, the coupons being  
20 identified by their coupon ID number.

In order to efficiently handle, classify, and store coupons, various metadata in a standardized format of the coupon is provided. One standardized format for the metadata could be XML (extended mark-up language).

Returning to Fig. 3, the coupon service server 200 transmits the coupon data through  
25 a firewall 210 to the Internet 220. The Internet 220 forward the data to a GGSN (gateway

GPRS (general packet radio service) support node) 230 which in turn transmits the data to a GPRS network operator 240.

The GPRS network operator 240 transmits the coupon data to an SGSN (serving GPRS support node) 250 which transmits the data via GPRS or 3G (third generation wireless communication) network 260, for example.

The network 260 transmits the data to wireless terminals 280 and 281 via BTS (base transceiver station) 270 and 271, respectively.

Alternatively, the coupon data can be transmitted only to wireless terminal 280 and then transmitted via various means which will be discussed subsequently to wireless terminal 281.

When the user of wireless terminal 281 wishes to redeem his or her electronic coupon at a retailer, the electronic coupon stored in his or her wireless terminal 281 is electronically transferred to the point-of-sale terminal 285 by various methods which will be discussed in detail later.

The redemption information contained in the point-of-sale terminal 285 is subsequently transferred to the retail chain corporate LAN (local area network) network 290 which compiles the coupon redemption information from all of its point-of-sale terminals and forwards this information to the coupon service server 200 via the firewall 295, Internet 220 and firewall 210.

Fig. 4 illustrates the data flow between a point-of-sale terminal and a wireless terminal via Bluetooth.

The following is a technology overview of the Bluetooth system.

The technology is an open specification for wireless communication of data and voice. It is based on a low-cost short-range radio link, built into a 9 x 9 mm microchip, facilitating protected ad hoc connections for stationary and mobile communication

environments. Bluetooth technology allows for the replacement of the many proprietary cables that connect one device to another with one universal short-range radio link. For instance, Bluetooth radio technology built into both the cellular telephone and the laptop would replace the cumbersome cable used today to connect a laptop to a cellular telephone.

- 5 Printers, PDA's, desktops, fax machines, keyboards, joysticks and virtually any other digital device can be part of the Bluetooth system. But beyond untethering devices by replacing the cables, Bluetooth radio technology provides a universal bridge to existing data networks, a peripheral interface, and a mechanism to form small private ad hoc groupings of connected devices away from fixed network infrastructures. Designed to operate in a noisy radio
- 10 frequency environment, the Bluetooth radio uses a fast acknowledgment and frequency hopping scheme to make the link robust. Bluetooth radio modules avoid interference from other signals by hopping to a new frequency after transmitting or receiving a packet. Compared with other systems operating in the same frequency band, the Bluetooth radio typically hops faster and uses shorter packets. This makes the Bluetooth radio more robust
- 15 than other systems. Short packages and fast hopping also limit the impact of domestic and professional microwave ovens. Use of Forward Error Correction (FEC) limits the impact of random noise on long-distance links. The encoding is optimized for an uncoordinated environment. Bluetooth radios operate in the unlicensed ISM band at 2.4 GHz. A frequency hop transceiver is applied to combat interference and fading. A shaped, binary FM
- 20 modulation is applied to minimize transceiver complexity. The gross data rate is 1Mb/s. A Time-Division Duplex scheme is used for full-duplex transmission. The Bluetooth baseband protocol is a combination of circuit and packet switching. Slots can be reserved for synchronous packets. Each packet is transmitted in a different hop frequency. A packet nominally covers a single slot, but can be extended to cover up to five slots. Bluetooth can
- 25 support an asynchronous data channel, up to three simultaneous synchronous voice channels,

or a channel which simultaneously supports asynchronous data and synchronous voice. Each voice channel supports 64 kb/s synchronous (voice) link. The asynchronous channel can support an asymmetric link of maximally 721 Kb/s in either direction while permitting 57.6 Kb/s in the return direction, or a 432.6 Kb/s symmetric link.

5           While Bluetooth has been discussed in detail above with regard to the present invention, it is to be understood that this is just for explanatory purposes. The present invention is not limited to the Bluetooth implementation.

          In operation, the wireless terminal 281 transmits the coupon ID and information to the point-of-sale terminal 285. The retail chain corporate LAN network 290, connected to  
10   the coupon service server 200 via the firewall 210, Internet 220, and firewall 295, verifies the coupon and calculates the discount/benefit in real time or as a batch daily. The coupon information is updated to the coupon service server as well as to the retail chain network server.

          Fig. 5 illustrates the data flow from a wireless terminal to point-of-sale terminal via  
15   optical bar codes.

          In operation, the wireless terminal 281 displays an optical bar code 288 containing coupon ID information on the screen of the wireless terminal 281. The point-of-sale terminal operator scans the bar code in Step 287 with the optical bar code scanner 286. The retail chain corporate LAN network 290 receives the information from the point-of-sale terminal  
20   285 and is connected to the coupon service server 200 via the firewall 295, Internet 220, and firewall 210 as with Fig. 4. The remainder of the operation is identical to that of the arrangement of Fig. 4.

          Fig. 6 illustrates the flow of data from a wireless terminal to a point-of-sale terminal via an infrared link. The operation of the system of Fig. 6 is the same as that of Fig. 4 with

the exception that the wireless terminal 281 is connected to the point-of-sale terminal 285 via infrared transceivers 330 and 310 and infrared link 320.

Fig. 7 illustrates the flow of data from a wireless terminal to a point-of-sale terminal via GPRS (general packet radio service).

5           In this arrangement, the wireless terminal 281 transmits the coupon ID information to the point-of-sale terminal 285 via the BTS 271, GPRS or 3G network 260, SGSN 250, GPRS network operator 240, GGSN 230, Internet 230, firewall 295, and the retail chain corporate LAN network 290. The path between the wireless terminal 281 and the Internet 220 may be the same path used to receive the coupon ID information from the coupon  
10   service server 200 as noted above with regard to Fig. 3.

The operation of the system illustrated in Fig. 7 is otherwise identical to that of Fig. 4 and accordingly, the details thereof have been omitted for the sake of brevity.

Fig. 8 illustrates the flow of data from one wireless terminal to another wireless terminal via GPRS.

15           As shown in Fig. 8, the wireless terminal 281 may transmit or forward coupon ID data contained therein to wireless terminal 280 via BTS 271, the GPRS or 3G network 260, and the BTS 270. Note that the wireless terminal 281 may have received the coupon ID data from the GPRS network operator 240 via the SGSN 250 and GPRS or 3G network 260 and BTS 271 as previously noted in the discussion of Fig. 3.

20           The coupons may be transmitted or forwarded to other terminals other than the wireless terminal 280 via the GPRS or 3G network 260.

Fig. 9 illustrates the flow of data from one wireless terminal to another wireless terminal via an infrared link.

25           In this arrangement, wireless terminal 281 is connected to wireless terminal 280 via infrared transceiver 330, infrared link 350 and infrared transceiver 340. The coupon ID and

information is transmitted from terminal to terminal via the infrared link 350. The visual/textual representation may be transmitted simultaneously between the wireless terminals via the infrared link or may be downloaded from the coupon service server 200 at a later time.

5        Fig. 10 illustrates the flow of data from one wireless terminal to another via Bluetooth. The connection between two or more wireless terminals such as 280 and 281 is established via the Bluetooth low-range radio link 400. The coupon ID/information is transmitted from terminal 281 to terminal 280 via the Bluetooth link 400 and the visual/textual representation may be transmitted simultaneously or may be downloaded from  
10      the coupon service server 200 at a later time.

      Fig. 11 illustrates the flow of data from one wireless terminal to another wireless terminal utilizing optical bar code scanning. The coupon ID is displayed as a bar code on the screen of wireless terminal 280. An optical bar code scanner 420 imbedded in wireless terminal 281 is used to scan the bar code 288 which is displayed on the wireless terminal  
15      screen 410 of wireless terminal 280. Thus, the coupon ID is copied by wireless terminal 281. A network connection via GPRS, for example, may be used to verify the coupon immediately or at a later time period.

      Fig. 12 illustrates optically scanning a coupon ID from a print media source using a wireless terminal. Namely, a coupon is printed in a magazine, newspaper, leaflet, etc., the  
20      coupon including a coupon ID printed in a bar code format 288. The wireless terminal 281 performs the Step 420 of scanning the printed bar code having the coupon ID utilizing an optical bar code reader imbedded in the wireless terminal 281.

      Once the coupon ID has been scanned by the wireless terminal 281, it may be stored and/or a visual and textual representation may be downloaded from the coupon service server  
25      200 via the GPRS-Internet connection 450. By this technique, the user of the wireless

terminal 281 may also take advantage of printed coupons without having to resort to the inefficient conventional steps used to redeem paper coupons.

Fig. 13 illustrates the transmission of an electronic coupon utilizing a Bluetooth transmitter.

5           As the user of the wireless terminal 281 comes in proximity to a physical point of interest where a Bluetooth transmitter used to transmit an electronic coupons resides, the Bluetooth transmitter transmits coupon IDs or coupon information to the wireless terminal 281. The Bluetooth transmitter 460 receives the coupon IDs or coupon information from the coupon service server 200 via the firewall 210 and Internet 220.

10           In the case of only coupon IDs being transmitted by the Bluetooth transmitter 460, the coupon visual and textual representation is retrieved by the wireless terminal 281 from the coupon service server 200 via the GPRS-Internet connection 450.

          The Bluetooth transmitter 460 can be placed in a retail store, shopping mall, or any location where there is a reasonably large volume of traffic flow, such as an airport or  
15       subway station, thereby serving as an advertising medium in conjunction with some sort of visual display related to the electronically transmitted coupons.

          Fig. 14 illustrates the transmission of an electronic coupon to a wireless terminal via a GPRS network.

          The coupon ID and coupon information, and optionally the visual and textual  
20       representation thereof, are delivered to the wireless terminal 281 via the GPRS or 3G network 260 which is connected to the coupon service server 200 via the firewall 210, Internet 220, GGSN 230, GPRS network operator 240, and SGSN 250. The coupon ID and the representation can either be transmitted simultaneously or maybe transmitted at separate times.

This concludes the description of the example embodiments. Although the present invention has been described with reference to a number of illustrative embodiments thereof, it should be understood that numerous other modifications and embodiments can be devised by those skilled in the art that will fall within the spirit and scope of the principles of this invention. More particularly, reasonable variations and modifications are possible in the component parts and/or arrangements of the subject combination arrangement within the scope of the foregoing disclosure, the drawings, and the appended claims without departing from the spirit of the invention. In addition to variations and modifications in the components and/or arrangements, alternative uses will also be apparent to those skilled in the art.

For example, while various electronic transmission elements and methods have been disclosed, the present invention should not be construed as being limited to those disclosed methods and equipment. Although the Internet has been discussed above as a communications path, it is to be understood that the present invention should in no way be construed as being limited thereto. For example, a wireless LAN (Local Area Network) path could also be used.



What is claimed is:

1. An electronic couponing method comprising the steps of:
  - transferring coupon information to a first portable terminal and storing same therein;
  - displaying a representation of the transferred coupon information on the first portable terminal; and
  - transferring at least part of the stored coupon information from the first portable terminal to another terminal for redemption.
2. An electronic couponing method comprising the steps of:
  - transferring coupon information to a first portable terminal and storing same therein;
  - displaying a representation of the transferred coupon information on the first portable terminal; and
  - transferring at least part of the stored coupon information from the first portable terminal to a second portable terminal.
3. An electronic couponing system comprising:
  - a first portable terminal having a memory;
  - a first transfer unit for transferring coupon information to said first portable terminal, said first portable terminal storing same in said memory thereof;
  - a display disposed within said first portable terminal for displaying a representation of said transferred coupon information from said first portable terminal; and
  - a second transfer unit for transferring at least part of said stored coupon information to another terminal for redemption.
4. An electronic couponing system comprising:
  - a first portable terminal having a memory;

23 a first transfer unit for transferring coupon information to said portable terminal, said  
24 portable terminal storing same in said memory thereof;

25 a display disposed within said first portable terminal for displaying a representation  
26 of said transferred coupon information;

27 a second portable terminal; and

28 a second transfer unit for transferring at least part of said stored coupon information  
29 from said first portable terminal to said second portable terminal .

30 5. The method of claim 1, wherein at least part of the coupon information is  
31 transferred to the first portable terminal by optically scanning information with an optical  
32 scanner.

33 6. The method of claim 1, wherein at least part of the coupon information is  
34 transferred to the first portable terminal with a Bluetooth radio link.

35 7. The method of claim 1, wherein at least part of the coupon information is  
36 transferred to the first portable terminal via the Internet.

37 8. The method of claim 7, wherein at least part of the coupon information is  
38 transferred from the Internet to the first portable terminal via a wireless link.

39 9. The method of claim 1, wherein at least part of the stored coupon  
40 information is transferred from the first portable terminal to another terminal via optically  
41 scanning the displayed representation of the transferred coupon information on the portable  
42 terminal.

43 10. The method of claim 1, wherein at least part of the stored coupon  
44 information is transferred from the first portable terminal to another portable terminal via a  
45 Bluetooth radio link.

11. The method of claim 1, wherein at least part of the stored coupon information is transferred from the first portable terminal to another terminal via an infrared link.

12. The method of claim 1, wherein at least part of the stored coupon information is transferred from the first portable terminal to another terminal via the Internet.

13. The method of 7, wherein at least part of the stored coupon information is transferred from the first portable to another terminal via the Internet via a wireless link.

14. The method of claim 2, wherein at least part of the coupon information is transferred to the first portable terminal by optically scanning information with an optical scanner.

15. The method of claim 2, wherein at least part of the coupon information is transferred to the first portable terminal with a Bluetooth radio link.

16. The method of claim 2, wherein at least part of the coupon information is transferred to the first portable terminal via the Internet.

17. The method of claim 2, wherein at least part of the coupon information is transferred from the Internet to the first portable terminal via a wireless link.

18. The method of claim 2, wherein at least part of the stored coupon information is transferred from the first portable terminal to a second portable terminal via the Internet.

19. The method of claim 18, wherein at least part of the stored coupon information is transferred from the first portable terminal to a second portable terminal via the Internet via a wireless link.

20. The method of claim 2, wherein at least part of the stored coupon information is transferred from the first portable terminal to a second portable terminal via an infrared link.

1           21.     The method of claim 2, wherein at least part of the stored coupon  
2     information is transferred from the first portable terminal to a second portable terminal via a  
3     Bluetooth radio link.

4           22.     The method of claim 2, wherein at least part of the stored coupon  
5     information is transferred from the first portable terminal to a second portable terminal via  
6     optically scanning the displayed representation of the transferred coupon information on the  
7     first portable terminal.

8           23.     The system of claim 3, wherein said first transfer unit comprises an optical  
9     scanner for optically scanning a representation of said coupon information.

10          24.     The system of claim 3, wherein said first transfer unit comprises a Bluetooth  
11     radio link.

12          25.     The system of claim 3, wherein said first transfer unit comprises the Internet.

13          26.     The system of claim 25, wherein said first transfer unit further comprises a  
14     wireless link.

15          27.     The system of claim 3, wherein said second transfer unit comprises an  
16     optical scanner for scanning the representation of said transferred coupon information on  
17     said display of said first portable terminal.

18          28.     The system of claim 3, wherein said second transfer unit comprises a  
19     Bluetooth radio link.

20          29.     The system of claim 3, wherein said second transfer unit comprises an  
21     infrared link.

22          30.     The system of claim 3, wherein said second transfer unit comprises the  
23     Internet.

1           31.     The system of claim 30, wherein said second transfer unit further comprises  
2     a wireless link.

3           32.     The system of claim 4, wherein said first transfer unit comprises an optical  
4     scanner for optically scanning a representation of said coupon information.

5           33.     The system of claim 4, wherein said first transfer unit comprises a Bluetooth  
6     radio link.

7           34.     The system of claim 4, wherein said first transfer unit comprises the Internet.

8           35.     The system of claim 33, wherein said first transfer unit further comprises a  
9     wireless link.

10          36.     The system of claim 4, wherein said second transfer unit comprises the  
11     Internet.

12          37.     The system of claim 36, wherein said second transfer unit further comprises  
13     a wireless link.

14          38.     The system of claim 4, wherein said second transfer unit comprises an  
15     infrared link.

16          39.     The system of claim 4, wherein said second transfer unit comprises a  
17     Bluetooth radio link.

18          40.     The system of claim 4, wherein said second transfer unit comprises an  
19     optical scanner for scanning said representation of said transferred coupon information on  
20     said display of said first portable terminal.

21          41.     An electronic couponing method comprising the steps of:  
22             transferring coupon information to a first portable terminal and storing same therein;  
23             displaying a representation of the transferred coupon information on the first  
24     portable terminal;

transferring at least part of the stored coupon information from the first portable terminal to another terminal for redemption; and

transferring at least part of the stored coupon information from the first portable terminal to a second portable terminal.

42. An electronic couponing system comprising:

a first portable terminal having a memory;

a first transfer unit for transferring coupon information to said first portable terminal, said first portable terminal storing same in said memory thereof;

a display disposed within said first portable terminal for displaying a representation of said transferred coupon information;

a second transfer unit for transferring at least part of said stored coupon information from said first portable terminal to another terminal for redemption;

a second portable terminal; and

a third transfer unit for transferring at least part said stored coupon information from said first portable terminal to said second portable terminal.

43. The method of claim 1, wherein said coupon information comprises a coupon ID (identification).

44. The method of claim 2, wherein said coupon information comprises a coupon ID (identification).

45. The method of claim 41, wherein said coupon information comprises a coupon ID (identification).

46. The system of claim 3, wherein said coupon information comprises a coupon ID (identification).

47. The system of claim 4, wherein said coupon information comprises a coupon ID (identification).

50           48.     The system of claim 42, wherein said coupon information comprises a  
51 coupon ID (identification).

52           49.     The method of claim 1, wherein at least part of the coupon information is  
53 transferred to the first portable terminal via a wireless LAN (Local Area Network).

54           50.     The method of claim 1, wherein at least part of the stored coupon  
55 information is transferred from the first portable terminal to another terminal via a wireless  
56 LAN (Local Area Network).

1           51.     The method of claim 2, wherein at least part of the coupon information is  
2 transferred to the first portable terminal via a wireless LAN (Local Area Network).

1           52.     The method of claim 2, wherein at least part of the stored coupon  
2 information is transferred from the first portable terminal to a second portable terminal via  
3 a wireless LAN (Local Area Network).

1           53.     The system of claim 3, wherein said first transfer unit comprises a wireless  
2 LAN (Local Area Network).

1           54.     The system of claim 3, wherein said second transfer unit comprises a  
2 wireless LAN (Local Area Network).

1           55.     The system of claim 4, wherein said first transfer unit comprises a wireless  
2 LAN (Local Area Network).

1           56.     The system of claim 4, wherein said second transfer unit comprises a  
2 wireless LAN (Local Area Network).

FIG. 1






FIG. 2







2/10

**FIG. 3**


3/10

**FIG. 4**

4/10

**FIG. 5**

5/10

**FIG. 6**

6/10






**FIG. 7**



FIG. 8



8/10


**FIG. 9****FIG. 10****FIG. 11**

9/10

**FIG. 12****FIG. 13**



10/10

**FIG. 14**



(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
21 June 2001 (21.06.2001)


PCT

(10) International Publication Number  
**WO 01/45061 A3**

- (51) International Patent Classification<sup>7</sup>: **G07G 1/14.** (72) Inventor: **RISSANEN, Jussi**; Pajalahdentie 6 A 18, FIN-00200 Helsinki (FI).
- (21) International Application Number: **PCT/IB00/01872**
- (22) International Filing Date:  
14 December 2000 (14.12.2000)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
09/461,353 15 December 1999 (15.12.1999) US
- (71) Applicant: **NOKIA CORPORATION [FI/FI]**; Keilalahdentie 4, FIN-02150 Espoo (FI).
- (71) Applicant (for LC only): **NOKIA INC. [US/US]**; 6000 Connection Drive, Irving, TX 75039 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,

[Continued on next page]

(54) Title: **WIRELESS ELECTRONIC COUPONING TECHNIQUE**



(57) Abstract: An electronic couponing technique includes transferring coupon information, which may include a coupon ID (identification) to a first portable terminal and storing same therein. The portable terminal displays a representation of the transferred coupon information on a display thereof. The stored coupon information may be transferred from the portable terminal to another terminal for redemption. The stored coupon information may also be transferred from the portable terminal to another portable terminal. Various schemes may be used to transfer the coupon information including a Bluetooth low-range radio link or an optical bar code scanner scanning an optical bar code or an infrared link or a wireless link from the portable terminal. The Internet or wireless LAN (Local Area Network) may also be used in transferring the coupon information to and from the various terminals.

WO 01/45061 A3



IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

(88) Date of publication of the international search report:  
18 April 2002

**Published:**

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/IB 00/01872

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 G07G1/14

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G07G G06F G07F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 97 21200 A (LEE CHONG U ;MOALLEMI KAMRAN (US); WARREN ROBERT L (US); SOLONA TE) 12 June 1997 (1997-06-12)	1,3,5,7, 25,30, 34,36, 43,46
Y	page 2, line 15 -page 4, line 14; figure 1	2,4,6,8, 10-21, 23,24, 26-29, 31-33, 35, 37-39, 41,42, 44,45, 47-56
	page 4, line 10-12 page 6, line 9-14 --- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- \*&\* document member of the same patent family

Date of the actual completion of the international search

1 February 2002

Date of mailing of the international search report

19/02/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Laub, C

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/IB 00/01872

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y A	US 5 420 606 A (GEIGER MARK A ET AL) 30 May 1995 (1995-05-30) column 4, line 60-67; claim 9; figure 1	11,29 1,5,20, 38
Y A	US 5 979 757 A (MURRAH JUDITH ET AL) 9 November 1999 (1999-11-09) column 1, line 30-40; figure 3  column 2, line 12-15	6,8,12, 13,19, 23,26,27 5,15,17, 18,21, 31,32, 35,37
Y          A	EP 0 950 968 A (MATSUSHITA ELECTRIC IND CO LTD) 20 October 1999 (1999-10-20)      figure 2A  US 5 657 317 A (BUNTE ALAN G ET AL) 12 August 1997 (1997-08-12)  abstract; claim 6; figure 1B	2,4, 14-18, 20,21, 31-33, 35, 37-39, 41,42, 44,45, 47,48, 51,52, 55,56  10,24, 28,33, 39,49, 50,53,54 17,39, 51,52,56

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IB 00/01872

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9721200	A	12-06-1997	AU 1279897 A EP 0871944 A2 WO 9721200 A2	27-06-1997 21-10-1998 12-06-1997
US 5420606	A	30-05-1995	CA 2117716 A1 DE 4433569 A1 GB 2282253 A ,B HK 1000329 A1 JP 2712139 B2 JP 7182564 A	21-03-1995 23-03-1995 29-03-1995 27-02-1998 10-02-1998 21-07-1995
US 5979757	A	09-11-1999	US 5825002 A US 6199753 B1 US 6330244 B1 US 5979753 A US 6084528 A	20-10-1998 13-03-2001 11-12-2001 09-11-1999 04-07-2000
EP 0950968	A	20-10-1999	AU 8648498 A EP 0950968 A1 CN 1246941 T WO 9909502 A1	08-03-1999 20-10-1999 08-03-2000 25-02-1999
US 5657317	A	12-08-1997	US 5555276 A US 5602854 A US 5365546 A US 5052020 A AU 700800 B2 AU 3145895 A AU 715628 B2 AU 9815198 A CA 2195661 A1 EP 0784893 A1 WO 9603823 A1 US 5790536 A US 5726984 A US 5949776 A AU 6987694 A CA 2184811 A1 WO 9427382 A1 WO 9524074 A1 US 5912926 A US 5696903 A CA 2162722 A1 AU 696841 B2 AU 5986994 A CA 2152598 A1 EP 0681762 A1 WO 9415413 A1 US 5673031 A US 5708680 A US 5844893 A US 5940771 A CA 2074169 A1 EP 0511295 A1 US 5331136 A WO 9111065 A1 US 5680633 A US 5567925 A	10-09-1996 11-02-1997 15-11-1994 24-09-1991 14-01-1999 22-02-1996 03-02-2000 04-03-1999 08-02-1996 23-07-1997 08-02-1996 04-08-1998 10-03-1998 07-09-1999 12-12-1994 08-09-1995 24-11-1994 08-09-1995 15-06-1999 09-12-1997 24-11-1994 17-09-1998 19-07-1994 07-07-1994 15-11-1995 07-07-1994 30-09-1997 13-01-1998 01-12-1998 17-08-1999 19-07-1991 04-11-1992 19-07-1994 25-07-1991 21-10-1997 22-10-1996

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IB 00/01872

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5657317	A	US 5679943 A	21-10-1997
		US 5949056 A	07-09-1999
		US 5218187 A	08-06-1993
		US 5313053 A	17-05-1994
<hr/>			